

SikaFlow[®] 150

DECLARATION OF PERFORMANCE No. DE0297/02

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	DE0297/02
2	INTENDED USE/S	Anchoring product, Principle 4.2
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 2+, System 4 (Reaction to fire)
5a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	0921

Declaration of Performance

SikaFlow[®] 150
DE0297/02
2024.03 , ver. 1
1713

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	NPD	System 4	EN 1504-6:2006
Pull- out strength	≤ 0,6 mm	System 2+	
Chloride ion content	≤ 0,05 %	System 2+	
Glass transition temperature	47 °C	System 2+	
Durability/Creep under tensile load	≤ 0,6 mm	System 2+	
Dangerous substances	NPD	System 2+	

7 SPECIFIC TECHNICAL DOCUMENTATION

SA-107/24

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jürgen Baumann
Head of Material testing and Analytics
Augsburg on 27 March 2024

Volker Schwarz
Head of Material Testing
Augsburg on 27 March 2024



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

SikaFlow® 150
DE0297/02
2024.03 , ver. 1
1713





24

Sika Services AG, Zurich, Switzerland

DoP No. DE0297/02

EN 1504-6:2006

Notified Body 0921

Anchoring product, Principle 4.2

Pull- out strength	≤ 0,6 mm
Chloride ion content	≤ 0,05 %
Glass transition temperature	47 °C
Durability/Creep under tensile load	≤ 0,6 mm

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance

SikaFlow® 150
DE0297/02
2024.03 , ver. 1
1713