

# PRODUCT DATA SHEET

# SikaProof® Sandwich Tape

# DOUBLE-SIDED ADHESIVE OVERLAP TAPE FOR THE SIKAPROOF A+ WATERPROOFING SYSTEM

## **DESCRIPTION**

SikaProof® Sandwich Tape is a double-sided adhesive tape based on a polyacrylic adhesive sandwiched between release liners.

#### **USES**

SikaProof® Sandwich Tape may only be used by experienced professionals.

Sealing overlap joints within the SikaProof® A+ membrane system

# **CHARACTERISTICS / ADVANTAGES**

- Good adhesion
- High durability
- Simple and fast to install

# **PRODUCT INFORMATION**

| Packaging           | 5 rolls packed in one cardboard box. Individual roll size:   |          |
|---------------------|--|----------|
|                     | Length   | 25 m     |
|                     | Width  | 50 mm    |
| Appearance / Colour | Transparent polyacrylic adhesive sandwiched between white release liners   |          |
| Shelf life          | 18 months from date of production  |          |
| Storage conditions  | Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +25 °C. Always refer to packaging.                                   |          |
| Dimensions          | Width  | 50 mm    |
|                     | Length   | 25 m     |
|                     | Thickness  | ~1,00 mm |
| SYSTEMS             |  |          |
| System Structure    | SikaProof® Sandwich Tape is a system component for sealing overlap joints of the SikaProof® A+ membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® A+ System |          |
| Compatibility       | For materials in direct contact (such as any synthetics etc.) the compatibility must be evaluated before full project application.  Contact Sika® Technical Services for more information.           |          |

Product Data Sheet SikaProof® Sandwich Tape June 2019, Version 02.01 020704210220000020

#### APPLICATION INFORMATION

| Ambient Air Temperature | -10 °C min. / +60 °C max. |
|-------------------------|---------------------------|
| Substrate Temperature   | +5 °C min. / +40 °C max.  |

#### APPLICATION INSTRUCTIONS

#### **SUBSTRATE QUALITY**

The contact surfaces must be dry, clean and free of materials that could impair the adhesion. Contaminants, such as dirt, dust, oil, bitumen and de-bonding agents, such as surfactants and silicones must be removed.

#### **APPLICATION METHOD / TOOLS**

Reference must be made to the Sika® Method Statement: SikaProof® A+ System and Product Data Sheets: SikaProof® A Membranes

#### **FURTHER INFORMATION**

■ Sika® Method Statement: SikaProof® A+

■ Product Data Sheets: SikaProof® A Membranes

# **IMPORTANT CONSIDERATIONS**

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

Do not install SikaProof® Sandwich Tape during continuous or prolonged rain or snowfall.

#### **BASIS OF PRODUCT DATA**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

# **ECOLOGY, HEALTH AND SAFETY**

#### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet.Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Italia S.p.A.

Via Luigi Einaudi, 6 20068 Peschiera Borromeo (MI) Phone: +39 02 54778 111 Fax: +39 02 54778 119 info@sika.it www.sika.it



QUALITY MANAGEMENT SYSTEM UNI EN ISO 9001:2008 CERTIFIED BY CERTIQUALITY N. 951

Product Data Sheet SikaProof® Sandwich Tape June 2019, Version 02.01 020704210220000020 SikaProofSandwichTape-en-IT-(06-2019)-2-1.pdf

