

PRODUCT DATA SHEET

Sikalastic® Carrier

GLASS REINFORCED CARRIER MEMBRANE FOR APPLICATION OF SIKAROOF® MTC AND SIKALASTIC® SYSTEM ON ROOF INSULATION BOARDS.

DESCRIPTION

Sikalastic® Carrier incorporates a dimensionally stable glass reinforcement and a modified elastomer coating, providing a highly effective carrier membrane.

USES

Sikalastic® Carrier is for use on Sikatherm® Insulation in the SikaRoof® MTC Cold Bonding Systems. Sikalastic® Carrier is suitable for use on boarded decks for the application of:

- SikaRoof® MTC 8, 12, 15, 18 and 22.
- Sikalastic®-614
- Sikalastic®-618
- Sikalastic®-641

CHARACTERISTICS / ADVANTAGES

- Easy and quick application
- Bridges joints of insulation boards
- Provides a smooth and uniform substrate

PRODUCT INFORMATION

Packaging	Roll width	20 m
	Roll length	1 m
	Roll weight	36 kg
Appearance / Colour	Black	
Shelf life	Product does not expire if correctly stored	
Storage conditions	The product must be stored properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures >+5 °C and <+35 °C.	

TECHNICAL INFORMATION

Tensile Strength	Longitudinal	300 N/50 mm
	Transverse	250 N/50 mm
Elongation at Break	Longitudinal	3 %
	Transverse	3 %

IMPORTANT CONSIDERATIONS

Limitations will be dictated by the individual Sikalastic® liquid being used – Please consult relevant PDS.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Italia S.p.A.

Via Luigi Einaudi, 6
20068 Peschiera Borromeo (MI)
Phone: +39 02 54778 111
Fax: +39 02 54778 119
info@sika.it
www.sika.it

Product Data Sheet
Sikalastic® Carrier
September 2019, Version 01.02
020915954000000001

SikalasticCarrier-en-IT-(09-2019)-1-2.pdf