

Sikalastic®-152

DECLARATION OF PERFORMANCE No. 91001207

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	91001207
2	INTENDED USE/S	EN 14891:2012 + EN 14891:2012/AC:2012 Liquid applied water impermeable product, based on polymer modified cementitious mortar for use in all external installations and swimming pools beneath ceramic tiling. Class CM O2P
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 14891:2012 + EN 14891:2012/AC:2012
	Notified body/ies:	1599

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Initial tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$	System 3	EN 14891:2012 + EN 14891:2012/AC:2012
Waterproofing	No penetration and $< 20 \text{ g}$ weight gain	System 3	
Crack bridging ability under standard conditions (+23°C)	$\geq 0.75 \text{ mm}$	System 3	
Crack bridging ability at low temperature (-20°C)	$\geq 0.75 \text{ mm}$	System 3	
Tensile adhesion strength after heat ageing	$\geq 0.5 \text{ N/mm}^2$	System 3	
Tensile adhesion strength after water contact	$\geq 0.5 \text{ N/mm}^2$	System 3	
Tensile adhesion strength after contact with lime water	$\geq 0.5 \text{ N/mm}^2$	System 3	
Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5 \text{ N/mm}^2$	System 3	
Tensile adhesion strength after chlorinated water contact	$\geq 0.5 \text{ N/mm}^2$	System 3	
Release of dangerous substances	NPD	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Nome: Michele Stella
Funzione: PE Waterproofing

Nome: Salvatore Schirinzi
Funzione: General Manager

Peschiera Borromeo
25 March 2022


Peschiera Borromeo
25 March 2022



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikalastic®-152	EN 1504-2:2004	44527518
Sikalastic®-152	EN 1504-2:2004	0207010100200000431026
Sikalastic®-152	EN 14891:2012	0207010100200000431026

 13	
DoP No. 91001207	
Sika Services AG, Zurich, Switzerland	
EN 14891:2012 + EN 14891:2012/AC:2012	
1599	
Liquid applied water impermeable product, based on polymer modified cementitious mortar for use in all external installations and swimming pools beneath ceramic tiling. Class CM O2P	
Initial tensile adhesion strength	≥ 0.5 N/mm ²
Waterproofing	No penetration and < 20 g weight gain
Crack bridging ability under standard conditions (+23°C)	≥ 0.75 mm
Crack bridging ability at low temperature (-20°C)	≥ 0.75 mm
Tensile adhesion strength after heat ageing	≥ 0.5 N/mm ²
Tensile adhesion strength after water contact	≥ 0.5 N/mm ²
Tensile adhesion strength after contact with lime water	≥ 0.5 N/mm ²
Tensile adhesion strength after freeze-thaw cycles	≥ 0.5 N/mm ²
Tensile adhesion strength after chlorinated water contact	≥ 0.5 N/mm ²
http://dop.sika.com	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Declaration of Performance

Sikalastic®-152
91001207
2022.03 , ver. 1
1026

Template for translation. Only for
internal use

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Italia S.p.A.
Via L. Einaudi, 6
20068 Peschiera Borromeo
(MI)
Italy
<http://dop.sika.com>

Declaration of Performance
Sikalastic®-152
91001207
2022.03 , ver. 1
1026

4/4

Template for translation. Only for
internal use

BUILDING TRUST

