

SikaFlow[®] 150

DECLARATION OF PERFORMANCE No. DE0294/03

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	DE0294/03
2	INTENDED USE/S	Structural bonding product for bonded mortar or concrete, Principle 4.4
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 2+, System 4 (Reaction to fire)
5a	HARMONISED STANDARD:	EN 1504-4:2004
	Notified body/ies:	0921

Declaration of Performance

SikaFlow[®] 150
DE0294/03
2024.03 , ver. 1
1713

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	NPD	System 4	EN 1504-4:2004
Bond/ adhesion strength	Pass	System 2+	
Shear strength	≥ 6 N/mm ²	System 2+	
Compressive strength	≥ 30 N/mm ²	System 2+	
Shrinkage/ expansion	≤ 0,1 %	System 2+	
Workability	60 minutes at 5 °C, 30 minutes at 20 °C, 10 minutes at 40 °C	System 2+	
Sensitivity to water	Pass	System 2+	
Modulus of elasticity	≥ 2000 N/mm ²	System 2+	
Coefficient of thermal expansion	≤ 100 x 10 ⁻⁶ /K	System 2+	
Glass transition temperature	≥ 40 °C	System 2+	
Durability	Pass	System 2+	
Dangerous substances	NPD	System 2+	

7 SPECIFIC TECHNICAL DOCUMENTATION

SA-107/24

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jürgen Baumann
 Head of Material testing and Analytics
 Augsburg on 27 March 2024

Volker Schwarz
 Head of Material Testing
 Augsburg on 27 March 2024




End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

SikaFlow® 150
 DE0294/03
 2024.03 , ver. 1
 1713





24

Sika Services AG, Zurich, Switzerland

DoP No. DE0294/03

EN 1504-4:2004

Notified Body 0921

Structural bonding product for bonded mortar or concrete, Principle 4.4

Bond/ adhesion strength	Pass
Shear strength	$\geq 6 \text{ N/mm}^2$
Compressive strength	$\geq 30 \text{ N/mm}^2$
Shrinkage/ expansion	$\leq 0,1 \%$
Workability	60 minutes at 5 °C, 30 minutes at 20 °C, 10 minutes at 40 °C
Sensitivity to water	Pass
Modulus of elasticity	$\geq 2000 \text{ N/mm}^2$
Coefficient of thermal expansion	$\leq 100 \times 10^{-6}/\text{K}$
Glass transition temperature	$\geq 40 \text{ °C}$
Durability	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

SikaFlow® 150

DE0294/03

2024.03 , ver. 1

1713

3/4

BUILDING TRUST



Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
SikaFlow® 150
DE0294/03
2024.03 , ver. 1
1713

4/4

BUILDING TRUST

